## **SLICE®** Complete Pack

## Exothermic portable cutting pack complete with it's own ignition source





SLICE Complete Pack

Go anywhere and cut, burn, or pierce virtually any metallic, non-metallic or composite material with this exothermic cutting pack.

A self-contained cutting system lends itself well to the emergency / forced entry type cutting situations where seconds count.

- Improved torch handle & rubber shield to improve the operators grip and provide protection from molten spray when piercing
- Improved striker assembly that incorporates a slide mechanism that allows the operator to only expose a small portion of the ignition bar (copper) which increases the life of the striker copper bar
- Improved battery box with improved features over prior model
  - Faster recharging of a "dead" battery
  - Better visual "gas gauge" indicating battery condition
  - Over-charging safe guard

Visit **esab.com** for more information.

## **Industry**

- Bridge Construction
- Industrial and General Fabrication
- Mining
- Repair and Maintenance
- Steel Erectors



## **SLICE®** Complete Pack

Specifications	
Main Voltage (Input)	120 V AC 60 Hz & 220 VAC 50 Hz
Output Voltage	12 V DC
Recharge Time (fully drained battery)	6 h
Exothermic Cutting Rods	1/4 in. x 22 in. Uncoated – 25 pieces
Length Of Power Cable & Oxygen Hose	3 m (10 ft.)
Power Cable AWG Size	#10
Certification Mark (Standards)	CE
Dimensions L x W H (Without Cylinder)	400.05 mm x 638.18 mm x 206.38 mm (15 in. x 25 in. x 8 in.)
Dimensions L x W H (With Cylinder)	400.05 mm x 688.98 mm x 206.38 mm (15 in. x 27 in. x 8 in.)
Weight Without Cylinder	17.71 kg (39.05 lbs.)
Weight With Cylinder	31.75 kg (70 lbs.)

Ordering Information		
SLICE Complete Pack – 220 V AC 50 Hz	63991042CE	

Options and Accessories	
SLICE Battery Ignition Source	96-076-040
Power Adapter w/ Europe Power Lead	96-076-042
SLICE Cutting Torch CE w/ #10 Power Cable (When Igniting w/ 12V Battery & Cutting w/o Power)	03-003-012CE
SLICE Cutting Torch CE w/ #6 (When Igniting 12V Battery & Cutting w/o Power)	03-003-011CE
SLICE Cutting Torch CE w/ #1 (Up to 200 A w/ Power)	03-003-010CE
SLICE Striker Assembly	72-012-010

Cutting Rods	
SLICE Exothermic Cutting Rods, Flux Coated, 1/4 x 22 - 100 Pcs	42049003
SLICE Exothermic Cutting Rods, Flux Coated, 1/4 x 22 - 25 Pcs	42049002
SLICE Exothermic Cutting Rods, Uncoated, 3/8 x 36 - 25 Pcs	43049009
SLICE Exothermic Cutting Rods, Uncoated, 3/8 x 18 - 50 Pcs	43049007
SLICE Exothermic Cutting Rods, Uncoated, 1/4 x 22 - 25 Pcs	43049002
SLICE Exothermic Cutting Rods, Uncoated, 1/4 x 44 - 25 Pcs	43049005
SLICE Exothermic Cutting Rods, Flux Coated, 3/8 x 18 - 50 Pcs	42049005
SLICE Exothermic Cutting Rods, Uncoated, 1/4 x 22 - 100 Pcs	43049003

ESAB / esab.com







